

AS 660

Street Sweeper



The AS 660 is an extremely powerful and efficient truck-mounted sweeper that is specially designed and perfectly matched to meet the needs of airports. With its rear suction unit and high suction power extending across the entire width of the vehicle, the AS 660 removes FOD (Foreign Objects Debris), leaves and dirt, plus liquids such as glycol or water, easily from the runway. Its operation is fully integrated into the super efficient and highly acclaimed ES control panel, enabling easy and straightforward control whilst driving.

Highlights

- Combination of linear and parallel lift enables flexible suspension and ensures tilt compensation when cornering and close proximity to the ground contour.
- Two-part suction shaft with adaptive ground adjustment
- Castor wheels improve running smoothness and enable ideal contour tracking.
- Lateral shift enables lateral adjustment when driving straight ahead and allows the rear suction nozzle to be positioned closer to the curb.
- Pressurised water recirculation system extends the operating time by up to 30%.

Your benefits

- Outstanding sweeping performance even when cornering, thanks to excellent coverage with disc brush, roller brush and suction nozzle, two-part suction nozzle and a flexible suspension.
- Greatly reduced brush wear, thanks to adjustable brush pressure and speed.
- Electrically controlled water jets with maximum flexibility through operation via the ES control panel.
- Dust-free collection of debris thanks to water jets in the suction shaft, on the disc brush and feed roller.
- Outstanding not only at airports, but ideal when clearing up on construction sites

Performance features

Cleaning concept

The AS 660 boasts outstanding suction power, a 9.2 yd³ hopper and a large water volume for long sweeping distances and maximum efficiency. With a self supporting frame, the sweeper can be mounted on any conventional two-axle truck chassis in either class 7 or 8, provided that the requirements for approval in terms of load capacity are met – a unique concept that offers maximum flexibility and adaptability.



Suction system

The rear suction unit enables full surface cleaning across the entire vehicle width. The high suction power and flow-optimised suction shaft ensure outstanding collection of debris – even persistent dirt and liquids. The flexible suspension, combined with a two-part suction vehicle, ensures that the suction nozzles ideally adjust to the swept surface, even when the truck is on a steep incline or uneven roads.

The transverse shift to the left or right enables lateral adjustment when driving straight ahead. The rear suction unit can therefore be positioned closer to the curb, while the corresponding pneumatic suspension also serves as lateral collision protection. The rear suction unit is not dependent on the type of truck and its



operation is fully integrated into the ES control panel, enabling simple and easy control whilse driving IPO.

Rear suction functions

- Lateral adjustment -80 /0/ +80
- Debris flap
- Inclination locking of the two suction shafts (locking of the center joint)
- Floating axle wheels on pivoted carrier rockers for optimal contour tracking in the driving direction
- Quick height adjustment on the floating axle
- Optional high-pressure spray bar, before or after the rear suction unit

Operation

State-of-the-art control technology is an important step towards safe and efficient sweeping. Logical and intuitive menu navigation and automatically controlled processes help drivers remain focused on the road.



Gallery







Related product

AS 990 / ASC 990 Street Sweeper



eCleango 550 Street Sweeper



Street King 660 Street Sweeper



Technical data

Hopper	
Tank volume	9.2 yd³
Tilt angle	60°
Sweeping unit	•
Disc brush diameter	21 / 25 in
Sweeping width	47.2 in
Sweeping width with suction nozzle and roller brush	92.5 in
Sweeping width rear suction unit	98.4 in
Sweeping width dual version	137.8 in
Roller brush diameter	15.7 in
Roller brush length	51.2 in
Suction unit	
Model	Rear suction unit
Suction hose diameter	9.8 in
Suction nozzle diameter	9.8 in
Suction fan	
Type of drive	Hydraulic motor
Max. air flow rate (free flow)	635,664 ft ³ /h
Speed	2,100 - 3,100 1/min
Water system	
Total water volume	422.7 gal
Drive system	
Drive	Auxiliary engine
Drive system - auxiliary engine	
Engine type	Deutz TCD 7.8 L6
Exhaust emission	Tier 4 final
After treatment system	DOC + DPF
Displacement	177 in ³
Torque	191.769 ft-lbs*
Speed range	1,600 1/min
Drive system - auxiliary engine 2	
Engine type	Deutz TD 2.9 L04
Exhaust emission	EuroMot IIIA
Displacement	177 in ³
Speed range	1,600 1/min
Hydraulic system	
Hydraulic tank volume	34.3 gal
Speed	
Transport speed	56 mph
Sweeping speed permanent use	12 mph
Weights	
Empty weight of the basic unit approx.	9,370 lb





Illustrations are not binding. Errors and amendments excepted.