



 **swenson**
a brand of aebi schmidt

EVA Auger

Spreader



The heavy-duty EVA Auger is designed to perform in the toughest conditions to get the job done. Designed for heavy-duty use in challenging conditions, it's well-suited for trucks in Class 6, 7, and 8 (20,000+ lbs. GVW). The quality manufacturing process ensures lasting, high-performance operation and it comes in configurations to fit your needs. Learn more about our advanced EVA and put one to work for you.

Highlights

- **Truck Compatibility:** Designed for trucks in Class 6, 7, and 8, with gross vehicle weight (GVW) exceeding 20,000 lbs
- **Dual Hydraulic Motors:** Two separate motors drive the auger and spinner disk for efficient and reliable operation
- **18" Carbon Spinner Disk:** Provides powerful material spread over large areas.
- **Heavy-Duty Auger:** A 7" hard-surfaced auger with multiple pitch lengths ensures durability and reliable performance
- **Heavy-Duty Drop-n-Loc Top Screen:** Protects the auger system from debris and other damage, ensuring long-term reliability

Your benefits

- **Hydraulic Interlock System:** Enhances safety by preventing access to the auger drive system while it's in operation
- **Standard Inverted Vee:** Keeps weight off the auger for optimal performance
- **Remote Grease Extension:** Facilitates easy lubrication of the front bearing, extending equipment life
- **Fast and Even Unloading:** Delivers fast and consistent unloading of material, ensuring efficiency

Performance features

Concept

The Swenson EVA Auger is built for outstanding performance and durability, providing a longer lifespan than many competitors. Its design focuses on ensuring that the machine can perform reliably in tough conditions while offering maximum efficiency.

Specifications

- **Sizes Available:** Ranges from 8' to 15' in length, with heights ranging from 48" to 70" Choose from widths of 82" or 84."
- **Capacity:** Capacities will vary depending on the determined length and height of your specific unit. There are many configurations available.
- **Construction:** Made from 10-gauge carbon steel with 7-gauge longitudinals, and 12-gauge stainless steel with 10-gauge longitudinals
- **Spread Width:** Between 4 to 40 feet for material distribution
- **Application Rate:** 400 to 900 lbs per lane mile
- **Safety Features:** Includes hydraulic interlock and Drop-n-Loc top screens to ensure safe operation
- **Warranty:** Comes with a 1-year limited warranty



Options

Pre-wet systems, tarp kit, tie-down kit, vibrator kit, cab shield, leg stands, sloped front, rubber side shields, and observation platform.

Related products

EV Select

Spreader



EV Dual Auger

Spreader





Trust in our many years of uniquely diverse experience. **Get in touch with us.** We'll find the right solution for your specific challenge.



Technical data

Hopper

Hopper capacity	3 - 9 m ³
-----------------	----------------------

Conveyor system

Conveyor system	Auger
-----------------	-------

Mounting/demount system

Mounting/demount system	Demount legs / Fixed-mounted
-------------------------	------------------------------

Drive system

Type of drive	Vehicle hydraulics
---------------	--------------------



Aebi Schmidt Holding AG
Leutschenbachstrasse 52
CH-8050 Zurich, Switzerland
Phone: +41 44 308 58 00
www.aebi-schmidt.com

© Aebi Schmidt Group
All rights reserved.
Technical data is subject to change.
Illustrations are not binding.
Errors and amendments excepted.

Document created on 11 APR 2025

